



US005870912A

United States Patent [19]
Vito

[11] **Patent Number:** **5,870,912**
 [45] **Date of Patent:** **Feb. 16, 1999**

[54] **ANTI-THEFT BRAKE LOCKING DEVICE**

[75] **Inventor:** Robert A. Vito, Berwyn, Pa.

[73] **Assignee:** ~~Lawson-Armor Corporation, Berwyn, Pa.~~

[21] **Appl. No.:** 949,009

[22] **Filed:** Oct. 10, 1997

[51] **Int. Cl.⁶** **F16H 57/00**

[52] **U.S. Cl.** **70/202; 70/201; 70/237**

[58] **Field of Search** **70/198-204, 209, 70/237, 238**

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,779,435	10/1988	Farrow	70/202 X
5,267,458	12/1993	Heh	70/202 X
5,282,373	2/1994	Riccitelli	70/209
5,537,846	7/1996	Simon	70/201 X

5,678,433	10/1997	Riccitelli	70/209
5,704,233	1/1998	Farshad	70/199 X
5,715,710	2/1998	DeLucia et al.	70/201 X

Primary Examiner—Suzanne Dino Barrett
Attorney, Agent, or Firm—Scott J. Fields, Esq.; Klehr, Harrison, Harvey, Branzburg & Ellers, LLP

[57] **ABSTRACT**

A device for locking the brake of a vehicle and preventing its theft comprising: a base member for a placement on the floorboard of a vehicle beneath a brake pedal; a U-shaped housing extending downward and having a first arm attached to the base and having a second shorter arm defining a gap for receipt of a brake pedal shaft, said space between the first and second arms defining a slot for receiving the brake pedal shaft and permitting its full extension upward through said shaft; and locking means associated with the second arm for locking the underside of the pedal within the slot such that the brake pedal cannot be depressed.

7 Claims, 2 Drawing Sheets

